


COBAmat® Standard

Standing the test of time, our original safety matting



- The original premium multi-purpose safety mat widely used across industry today.
- An ideal choice for longer production lines, or for covering mezzanine floors.
- Available in four vibrant colours and four weave (hole) sizes to suit the application.
- Vinyl strips are interwoven, rather than welded, for better flexibility and lower risk of breaking.
- Cross-ribbed grip to reduce slipping.
- Fully reversible for added longevity.
- Suitable for use in wet and dry environments, or where swarf and debris cause problems.
- Fire tested to BS EN 13501-1 and slip tested to DIN 51130.
- The largest hole size available in COBAmat, this matting is ideally suited to trapping swarf and larger debris particles.
- Commonly used in areas such as machine shops with lathes, assembly/finishing areas where offcuts and debris may be present.
- 22 mm x 22 mm hole size.



Parts

Part Number	Size	Colour	Weight (kg)
CS010605	0.6 m x 5 m	Black	13
CS010610	0.6 m x 10 m	Black	26
CS010905	0.9 m x 5 m	Black	20
CS010905	0.9 m x 5 m	Black	20
CS010910	0.9 m x 10 m	Black	40
CS011210	1.2 m x 10 m	Black	56
CS011205	1.2 m x 5 m	Black	28
CS011210	1.2 m x 10 m	Black	56
CS020605	0.6 m x 5 m	Blue	13
CS020610	0.6 m x 10 m	Blue	26

Technical Specifications

Material	PVC
Surface Finish	Cross ribbed lattice
Product Height	12 mm
Hole Size	22 mm x 22 mm
Min. Operating Temperature	-20°C
Max. Operating Temperature	+60°C
Resistance to Chemicals	PVC is resistant to many different chemicals, alkalis and general industrial chemicals. PVC resists alcohols, aliphatic hydrocarbons, oils, weak acids,

Part Number	Size	Colour	Weight (kg)
CS021205	1.2 m x 5 m	Blue	28
CS020905	0.9 m x 5 m	Blue	20
CS020910	0.9 m x 10 m	Blue	40
CS030610	0.6 m x 10 m	Red	26
CS021205	1.2 m x 5 m	Blue	28
CS021210	1.2 m x 10 m	Blue	56
CS030605	0.6 m x 5 m	Red	13
CS030610	0.6 m x 10 m	Red	26
CS030905	0.9 m x 5 m	Red	20
CS030910	0.9 m x 10 m	Red	40
CS031205	1.2 m x 5 m	Red	28
CS031210	1.2 m x 10 m	Red	56
CS040605	0.6 m x 5 m	Green	13
CS040610	0.6 m x 10 m	Green	26

strong mineral acids and alkalis. PVC resists oil and grease if properly cleaned. PVC does not resist organic solvents, ketones, esters and aromatic hydrocarbons. Please contact us for more specific details

Environmental Resistance	Suitable for wet and dry environments, indoors or outdoors
UV Resistance	Resistant to UV, but please note that red is not colourfast in direct sunlight
Typical Applications	General industrial, Engineering, Machine tool areas where swarf prevalent
Installation Method	Loose lay, reversible
Accessories	Factory fitted edging where required
Cleaning Method	Pressure hose with mild detergent if required
COO (Country of Origin)	UK
Slip Tested to	DIN 51130 - R10

Additional Information



Workstation Ramp Slip Test DIN 51130



Workstation Fire Test EN ISO 11925



Workstation Fire Test EN ISO 9239



Workstation Fire Test BS EN 13501

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@cobaeurope.com

www.cobaeurope.com