



## EPDM Rubber

Excellent resistance to ozone, oxidants, water and harsh weather conditions



- High performing all rounder, ideal for marine and outdoor applications.
- Common uses include; seals, o-rings, glass-run channels, radiators, garden and appliance hose, tubing, pond liners, washers, belts and electrical insulation.
- 67 degrees shore A hardness.
- Tensile strength at break: 5.0 Mpa.
- Elongation at break: 300%.

## Parts

Part Number	Size	Colour	Weight (kg)
EPDM00001	1.4 m x 10 m x 1.5 mm	Black	37
EPDM00002	1.4 m x 10 m x 3 mm	Black	63.3
EPDM00003	1.4 m x 10 m x 4.5 mm	Black	91
EPDM00004	1.4 m x 10 m x 6 mm	Black	123

## Technical Specifications

<b>Material</b>	EPDM and SBR
<b>Surface Finish</b>	Smooth
<b>Product Height</b>	1 mm-25 mm
<b>Roll Length</b>	5 m, 10 m
<b>Min. Operating Temperature</b>	-30°C
<b>Max. Operating Temperature</b>	+80°C
<b>Other Product Performance Information</b>	Test Temperature: 25°C Relative Humidity: 35% Correlation criterion: GB/T528-1998 GB/T3512-1989 GB/T531-1992
<b>COO (Country of Origin)</b>	CN