



## COBAwash®

A real asset in floor protection for domestic and commercial use



- Easy to clean, practical and machine washable.
- Easy care, smaller sizes\* can be washed in a domestic washing machine. (All sizes can be washed in an industrial washing machine.)
- Carpet pile can retain up to 3.5 litres/ m<sup>2</sup> of moisture.
- Also traps up to 800g of debris/dry dust.
- Bleach and fade resistant – 11-year warranty against significant colour loss.



### Styles Available



Blue



Grey



Red



Brown

## Parts

Part Number	Size	Colour	Weight (kg)
LM010201	0.6 m x 0.85 m	Black/Blue	1.25
LM010202	0.85 m x 1.5 m	Black/Blue	3
LM010203	1.15 m x 1.75 m	Black/Blue	4.75
LM010204	0.85 m x 1.2 m	Black/Blue	2.4
LM010301	0.6 m x 0.85 m	Black/Red	1.25
LM010302	0.85 m x 1.5 m	Black/Red	3
LM010303	1.15 m x 1.75 m	Black/Red	4.75
LM010304	0.85 m x 1.2 m	Black/Red	2.4
LM010501	0.6 m x 0.85 m	Black/Brown	1.25
LM010502	0.85 m x 1.5 m	Black/Brown	3
LM010503	1.15 m x 1.75 m	Black/Brown	4.75
LM010504	0.85 m x 1.2 m	Black/Brown	2.4
LM010601	0.6 m x 0.85 m	Black/Steel	1.25
LM010602	0.85 m x 1.5 m	Black/Steel	3
LM010603	1.15 m x 1.75 m	Black/Steel	4.75
LM010604	0.85 m x 1.2 m	Black/Steel	2.4

## Technical Specifications

<b>Material</b>	PA
<b>Backing</b>	NBR
<b>Surface Finish</b>	Straight set
<b>Product Height</b>	8 mm
<b>Product Weight</b>	2.3 kg / m <sup>2</sup>
<b>Roll Length</b>	N/A
<b>Mat Edge</b>	NBR 20 mm
<b>Pile Weight</b>	0.65 kg / m <sup>2</sup>
<b>Min. Operating Temperature</b>	0°C
<b>Max. Operating Temperature</b>	+60°C
<b>Resistance to Chemicals</b>	Rubber is resistant to many chemicals, alkalis, detergents and general industrial chemicals. Rubber may swell in polar solvents.
<b>Environmental Resistance</b>	Suitable for indoor environments
<b>UV Resistance</b>	No
<b>Typical Applications</b>	Entrance areas
<b>Installation Method</b>	Loose lay
<b>Cleaning Method</b>	0.6 m x 0.85 m and 0.85 m x 1.2 m can be washed in standard domestic washing machines. All other sizes can be laundered in commercial washing machines.
<b>COO (Country of Origin)</b>	UK
<b>Guarantee</b>	2 years against manufacturing defects. 11 year against colour loss, subject to washing instructions being adhered too.
<b>Colour fastness to light</b>	5
<b>Colour fastness to rubbing, wet and dry</b>	5
<b>Colour fastness to water</b>	5
<b>Colour fastness to soiling</b>	5
<b>Electrostatic charging</b>	ISO 6356 (2012) Determination of the static electrical propensity walking test - 0.3kVolts

